

Leica FlexLine TS03/TS07 Manual Total Stations



FlexLine



LEICA FLEXLINE TS03/TS07 MANUAL TOTAL STATIONS

- **Work faster:** measure more points per day due to faster measurement and stakeout procedures (endless drives, trigger key, drives on both sides, pinpoint EDM and more), supported by our comprehensive and user-friendly Leica FlexField software.
- **Use it trouble-free:** increase productivity and minimise downtime by relying on instruments that simply work and come with a global service and support network.
- **Choose products that are built to last:** FlexLine operates with the same high level of quality even after years of use under harsh conditions (like mud, dust, blowing rain, extreme heat and cold).
- **Control your investment:** reliability, speed and accuracy ensure a lower investment over the product lifetime and a higher resell value.
- **Save time with AutoHeight:** measure, read and set the instrument height automatically with this revolutionary feature in the FlexLine TS07 (optional). Errors are minimised and the setup process onsite is faster.

The Leica FlexLine TS03 and TS07 high-quality, manual total stations are based on a proven product concept that has been revolutionising the world of measurement and survey for nearly 200 years. The instruments are equipped with a comprehensive application-based software package - Leica FlexField software - that enables most survey and stakeout tasks to be carried out easily and efficiently. The new FlexLine manual total stations work reliably and deliver accurate results even in harsh environments.

leica-geosystems.com



- when it has to be **right**

Leica
Geosystems

PART OF
HEXAGON

Leica FlexLine TS03/TS07



Leica FlexLine TS03



Leica FlexLine TS07

ANGULAR MEASUREMENT

Accuracy Hz and V	Absolute, continuous, diametrical ¹	2" / 3" / 5"	1" / 2" / 3" / 5" / 7"
	<ul style="list-style-type: none"> ■ Display resolution: 0.1" (0.1 mgon) ■ Quadruple axis compensation ■ Compensator setting accuracy²: 0.5" / 1" / 1.5" / 2" ■ Compensator range: +/- 4' ■ Electronic level resolution: 2" ■ Circular level sensitivity: 6' / 2 mm 	✓	✓

DISTANCE MEASUREMENT

Range	<ul style="list-style-type: none"> ■ Prism (GPR1, GPH1P): 0.9 m to 3,500 m ■ Prism GPR1 (Long Range mode) > 10,000 m 	✓	✓
	Non-Prism / Any surface <ul style="list-style-type: none"> ■ R500³ ■ R1000⁴ 	✓ ✗	✓ •
Accuracy / Measurement time	Single prism <ul style="list-style-type: none"> ■ Precise+ / Once: 1 mm + 1.5 ppm (typical 2.4 s) ■ Precise&Fast / Once&Fast: 2 mm + 1.5 ppm (typical 2 s) ■ Tracking / Continuously: 3 mm + 1.5 ppm (typical < 0.15 s) ■ Averaging: 1 mm + 1.5 ppm ■ Long Range mode / > 4 km: 5 mm + 2 ppm (typical 2.5 s) 	✓	✓
	Non-Prism / Any surface <ul style="list-style-type: none"> ■ 0 m - 500 m: 2 mm + 2 ppm (typical 2.4 s⁵) ■ > 500 m: 4 mm + 2 ppm 	✓	✓
Laser dot size	<ul style="list-style-type: none"> ■ At 30 m: 7 mm x 10 mm ■ At 50 m: 8 mm x 20 mm ■ At 100 m: 16 mm x 25 mm 	✓	✓
Telescope	<ul style="list-style-type: none"> ■ Magnification: 30x ■ Resolving power: 3" ■ Focusing range: 1.55 m / 5.08 ft to infinity ■ Field of view: 1°30' / 1.66 gon / 2.7 m at 100 m 	✓	✓

GENERAL

Display and keyboard		3.5" (inch), 320 x 240 px QVGA, grayscale, 28 keys ^{6a}	3.5" (inch), 320 x 240 px QVGA, colour, touch, 28 keys ^{6b}
	2 nd keyboard	✗	•
	Key illumination	✗	✓
Operation	<ul style="list-style-type: none"> ■ Endless drives for HZ & V ■ Trigger-Key: user definable with 2 functions 	✓	✓
Power management	Exchangeable Lithium-Ion battery⁷ <ul style="list-style-type: none"> ■ Operating time with GEB364 ■ Operating time with GEB334 	up to 32 h up to 16 h	up to 32 h up to 16 h
	Battery charging time with <ul style="list-style-type: none"> ■ GKL341 charger for GEB364 / GEB334 ■ GKL311 charger for GEB364 / GEB334 	3 h 30 min / 3 h 6 h 30 min / 3 h 30 min	3 h 30 min / 3 h 6 h 30 min / 3 h 30 min
	External supply voltage <ul style="list-style-type: none"> ■ Nominal voltage 13.0 V DC & 16 W max 	✓	✓
Data storage	<ul style="list-style-type: none"> ■ Internal memory: 4 GB Flash ■ Memory card: SD card 1 GB or 8 GB ■ USB memory stick: 1 GB 	✓	✓
Processor	<ul style="list-style-type: none"> ■ TI OMAP4430 1GHz Dual-core ARM® Cortex™ A9 MPCore™ ■ Operating system – Windows EC7 	✓	✓
Interfaces	<ul style="list-style-type: none"> ■ RS232⁸, USB device ■ Bluetooth®⁹, WLAN¹⁰ 	✓ ✗	✓ ✓
	Mobile Data sidecover: LTE-Modem for internet access <ul style="list-style-type: none"> ■ Working range: 5 m to 150 m ■ Position accuracy: 5 cm at 100 m ■ Wavelength red /orange: 617 nm / 593 nm 	✗	✓ (R1000)
Laser plummet (Laserclass 2)	Accuracy <ul style="list-style-type: none"> ■ Plumb line deviation: 1.5 mm at 1.5 m instrument height ■ Diameter of laser point: 2.5 mm at 1.5 m instrument height 	✓	✓
AutoHeight module for automatic instrument height measurement (Laserclass 2)	Accuracy <ul style="list-style-type: none"> ■ Distance accuracy: 1.0 mm (1 Sigma) ■ Distance range: 0.7 m to 2.7 m 	✗	•
Weight	<ul style="list-style-type: none"> ■ Working temperature range: -20°C to +50°C¹¹ 	4.3 kg	4.3 - 4.5 kg
Environmental specifications	<ul style="list-style-type: none"> ■ Arctic version: -35°C to +50°C ■ Dust / Water (IEC 60529) / Humidity: IP66 / 95%, non-condensing ■ Military Standard 810G, Method 506.5 	✓ ✗ ✓	✓ • ✓
LOC8	Tracking and theft deterrence device	•	•

Legend:

1. 1" (0.3 mgon), 2" (0.6 mgon), 3" (1 mgon), 5" (1.5 mgon), 7" (2 mgon)
2. Angular accuracy / Compensator setting accuracy: 1" / 0.5" (0.2 mgon), 2" / 0.5" (0.2 mgon), 3" / 1.0" (0.3 mgon), 5" / 1.5" (0.5 mgon), 7" / 2.0" (0.7 mgon)
3. R500: Kodak gray 90% reflective (0.9 m to >500 m), Kodak gray 18% reflective (0.9 m to >200 m)
4. R1000: Kodak gray 90% reflective (0.9 m to >1000 m), Kodak gray 18% reflective (0.9 m to >500 m)
5. Up to 50 m, max. measurement time 15 s

6. (a) Face I standard, (b) Face I standard, face II optional
7. Continuous angle measurement, new battery
8. 5 PIN Lemo-0 for power, communication and data transfer
9. For communication and data transfer
10. For internet access, communication and data transfer, WLAN range up to 200 m
11. Storage temperature: -40°C to +70°C

✓ = Included • = Optional ✗ = Not available



Laser radiation, avoid direct eye exposure.
Class 3R laser product in accordance with IEC 60825-1:2014.

The Bluetooth® trademarks are owned by Bluetooth SIG, Inc. Windows is a registered trademark of Microsoft Corporation. Other trademarks and trade names are those of their respective owners.

Copyright Leica Geosystems AG, 9435 Heerbrugg, Switzerland. All rights reserved.
Printed in Switzerland – 2022. Leica Geosystems AG is part of Hexagon AB. 876721en – 03.22

- when it has to be **right**



Leica Geosystems AG
Heinrich-Wild-Strasse
9435 Heerbrugg, Switzerland
+41 71 727 31 31

Coordinates Co., Ltd

09 250 299 877, 09 962 391 185
www.coordinatesmyanmar.com
SH-201, SH Building, Thitsar Oo Yin
Housing, Thitsar Road, (8) Quarter,
South Okkalapa Tsp, Yangon.