

Leica Nova TM60

Data sheet

Nova



Leica Geosystems' new monitoring solution comes with a strong promise: **real-time information and reports** you can always rely on, helping you make informed decisions in time and on time. Be it settling, flexing, shifting, sliding or any other change of state – you will have it **under control** 24 hours a day, seven days a week. The robust, precise and enduring TM60 comes with the world's longest **ATRplus range**, **half-second** automatic aiming accuracy, advanced **imaging** and the longest **continuous operation**. Combined with the **Leica GeoMoS monitoring solution**, you will be able to react to complex demands of any project – be it continuous or periodic. The decision is easy: maximum safety, minimum risk, half-second at a time.

LEICA NOVA TM60 MONITORING STATION: MONITOR IT.

- **Permanent monitoring (24/7):** remote operation, continuous monitoring, real-time measurement data, robust against various environmental conditions.
- **Campaign monitoring (periodical):** flexible instrument setup, automated measurements, Leica Captivate field software, dedicated monitoring app, connectivity to cloud services.
- **Buildings and structures:** monitoring of buildings, skyscrapers, industrial and sports facilities, offshore and underground structures.
- **Transportation infrastructure:** monitoring of tunnels, railway, bridges, roads & highways, airports, ports & canals.
- **Environmental monitoring:** monitoring of landslides, rock falls, subsidence.
- **Energy infrastructure:** monitoring of dams, oil & gas, nuclear facilities, pipelines power plants.
- **Mining:** monitoring of slope stability, high walls and quarries.

Leica Nova TM60 Monitoring Station

ANGLE MEASUREMENT

Accuracy ¹ Hz and V	■ Absolute, continuous, quadruple	0.5" (0.15 mgon) or 1" (0.3 mgon)
--------------------------------	-----------------------------------	-----------------------------------

DISTANCE MEASUREMENT

Range ²	■ Prism (GPR1, GPH1P) ³ ■ Non-Prism / Any surface ⁴	0.9 m to 3,500 m 0.9 m to >1,000 m
Accuracy / Measurement time	■ Single (prism) ^{2,5} ■ Single (any surface) ^{2,4,5,6}	0.6 mm + 1 ppm / typ. 2.4 s 2 mm + 2 ppm / typ. 2 s ⁹
Laser dot size	At 50 m	8 mm x 20 mm
Measurement technology	System analyser	Coaxial, visible red laser

IMAGING⁷

Overview and telescope camera	■ Sensor ■ Field of view (overview / telescope) ■ Frame rate	5 megapixel CMOS sensor 19.4° / 1.5° Up to 20 frames per second
-------------------------------	--	---

MOTORISATION

Direct drives based on Piezo technology	Rotation speed / Time to change face	Maximum 200 gon (180°) per s / typically 2.9 s
---	--------------------------------------	--

AUTOMATIC AIMING - LONG RANGE ATRplus

Target aiming range ²	■ Circular prism (GPR1, GPH1P) ■ 360° prism (GRZ4, GRZ122)	■ 3,000 m ■ 1,500 m
Accuracy ^{1,2} / Measurement time	ATRplus angle accuracy Hz, V	0.5" (0.15 mgon) or 1" (0.3 mgon) / typically 3-4 s

GENERAL

Operating System / Field Software	Windows EC7 / Leica Captivate with apps	
Processor	TI OMAP4430 1GHz Dual-core ARM® Cortex™- A9 MPCore™	
Autofocus ⁸ telescope	Magnification / Focus Range	30 x / 1.7m to infinity
Display and keyboard	5" (inch), WVGA, colour, touch, Face 1 standard, Face 2 optional	37 keys, illumination
Operation	3x endless drives, 1x Servofocus drive, 2x Autofocus keys ⁸ , user-definable SmartKey	
Power management	Exchangeable Lithium-Ion battery with internal charging capability	Operating Time up to 9 h
Data storage	■ Internal memory ■ Memory card	2 GB SD card 1 GB or 8 GB
Interfaces	RS232, USB, Bluetooth®, WLAN	
Weight	Total station including battery	7.2 kg
Environmental specifications	■ Working temperature range ■ Dust & Water (IEC 60529) / Blowing rain ■ Humidity	-20°C to +50°C IP65 / MIL-STD-810G, Method 506.5-I 95%, non-condensing

¹ Standard deviation ISO 17123-3

² Overcast, no haze, visibility about 40 km, no heat shimmer

³ 0.9 m to 2,000 m for 360° prisms (GRZ4, GRZ122)

⁴ Object in shade, sky overcast, Kodak Gray Card (90% reflective)

⁵ Standard deviation ISO 17123-4

⁶ Distance > 500 m: Accuracy 4 mm + 2 ppm, Measurement Time typ. 6 s

⁷ Available on TM60 I models

⁸ Autofocus for TM60 I models, Servofocus only for TM60 models

⁹ Up to 50 m, max. measurement time 15 s for full range



Laser radiation, avoid direct eye exposure.
Class 3R laser product in accordance with IEC 60825-1:2014.

The Bluetooth® trademarks are owned by Bluetooth SIG, Inc. Windows is a registered trademark of Microsoft Corporation. Other trademarks and trade names are those of their respective owners. Copyright Leica Geosystems AG, 9435 Heerbrugg, Switzerland. All rights reserved. Printed in Switzerland - 2020. Leica Geosystems AG is part of Hexagon AB. 929643en - 11.20



Integrate with LOC8 - Lock & Locate

For more information visit: leica-geosystems.com/LOC8